TÜRK STANDARDLARI ENSTİTÜSÜ

TÜRK STANDARDLARINA UYGUNLUK BELGESİ

TURKISH STANDARDS INSTITUTION

CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS

Markanın Tanımı Description of the Mark

TSE veya/or  veya/or TSE

BELGE NUMARASI *REFERENCE NUMBER OF LICENCE*	000134-TSE-06/09
BELGENİN İLK VERİLİŞ TARİHİ *DATE OF FIRST ISSUE OF LICENCE*	24.04.2012
BELGENİN SON GEÇERLİLİK TARİHİ *LICENCE VALID UNTIL*	24.04.2027
BELGE SAHİBİ KURULUŞUN ADI *NAME OF THE LICENCE HOLDER*	İZOCAM TİCARET VE SANAYİ ANONİM ŞİRKETİ
BELGE SAHİBİ KURULUŞUN ADRESİ *ADRESS OF THE LICENCE HOLDER*	ALTAYÇEŞME MAH. ÇAMLI SK. PASCO PLAZA /21 NO:4 MALTEPE İSTANBUL/TÜRKİYE
ÜRETİM YERİ ADI *NAME OF THE MANUFACTURING PLACE*	İZOCAM TİCARET VE SANAYİ ANONİM ŞİRKETİ TARSUS ŞUBESİ
ÜRETİM YERİ ADRESİ *ADRESS OF THE MANUFACTURING PLACE*	TARSUS-ADANA KARAYOLU ÜZERİ KONAKLAR KÖYÜ KELİ MEVKİİ TARSUS MERSİN / TÜRKİYE
İPTAL EDİLEN BELGE NUMARASI (Varsa) *INDICATION OF SUPERSEDED LICENCE (if any)*	000134-TSE-06/08
TESCİLLİ TİCARİ MARKASI *REGISTERED TRADE MARK*	izocam şekil
İLGİLİ TÜRK STANDARDI *RELATED TURKISH STANDARD*	TS EN 13162+A1 / 02.04.2015

TÜRKAK

Ürün
TS EN ISO/IEC 17065
AB-0105-U

BELGE KAPSAMI
SCOPE OF LICENCE

THERMAL INSULATION PRODUCTS FOR BUILDINGS - FACTORY MADE MINERAL WOOL (MW) PRODUCTS
1. COMMERCIAL MODEL: ROOF BLANKET (TYPE 300) - REACTION TO FIRE: A1 - THERMAL CONDUCTIVITY (λ) : 0. 036 W/mK - THICKNESS LEVEL: T1 - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD, - FACING: UNFACED. THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP, (Scope Change: 26.05.2022)
2. COMMERCIAL MODEL: ROOF BLANKET (TYPE 350) - REACTION TO FIRE: A1 - THERMAL CONDUCTIVITY (λ): 0,039 W/mK - THICKNESS LEVEL: T1 - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD - FACING: UNFACED. THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 21.04.2026)
3. COMMERCIAL MODEL: ROOF BLANKET (TYPE 300+) - REACTION TO FIRE: A1 – THERMAL CONDUCTIVITY (λ) : 0.035 W/mK - THICKNESS LEVEL: T1 - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD - FACING: FACED (BOTH SIDE GLASS TISSUE). THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP.

e-imzalı/e-signed

11.05.2026

On Behalf Of The Head Of Certification Center
FATİH KURT

TSE ADANA CERTIFICATION DIRECTOR

*This certificate also shows that the production place of the certified product meets the requirements of Institute.
*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.
*TSE * Address: Yakapınar Mah. D-400 Bulvarı No:174 Yüreğir * Telephone: 03224581940-41* Fax: 03224588243
*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail :bmb@tse.org.tr , web : www.tse.org.tr

TÜRK STANDARDLARI ENSTİTÜSÜ

TÜRK STANDARDLARINA UYGUNLUK BELGESİ

TURKISH STANDARDS INSTITUTION

CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS

Markanın Tanımı Description of the Mark

TSE veya/or  veya/or TSE

(000134-TSE-06/09nolu belge devamı) : İZOCAM TİCARET VE SANAYİ ANONİM ŞİRKETİ

İLGİLİ TÜRK STANDARDI(*RELATED TURKISH STANDARD*) TS EN 13162+A1 / 02.04.2015

4. COMMERCIAL MODEL: WALL BOARD: - REACTION TO FIRE: A1 - THERMAL CONDUCTIVITY (λ) : 0.035 W/mK - THICKNESS LEVEL: T3 - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD - FACING: UNFACED, THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP.
5. COMMERCIAL MODEL: WALL BOARD: - REACTION TO FIRE: A1 – THERMAL CONDUCTIVITY (λ) : 0.035 W/mK - THICKNESS LEVEL: T3- DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD -FACING: FACED (BOTH SIDE GLASS TISSUE). THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP.
6. COMMERCIAL MODEL: ROOF BLANKET (TYPE 400) - REACTION TO FIRE: A1, - THERMAL CONDUCTIVITY (λ) :0.044 W/mK - THICKNESS LEVEL: T1 - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD - FACING: UNFACED. THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 24.10.2018)
7. COMMERCIAL MODEL: "PARTITION WALL BOARD"- REACTION TO FIRE: A1 - THERMAL CONDUCTIVITY (λ) :0.037 W/mK- THICKNESS LEVEL: T3 - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD - FACING: UNFACED. THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 24.10.2018)
8. COMMERCIAL MODEL: "PARTITION WALL BOARD R+" - REACTION TO FIRE: A1 - THERMAL CONDUCTIVITY (λ): 0.035 W/mK - THICKNESS LEVEL: T3 - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD, FACING: UNFACED. THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 24.10.2018)
9. COMMERCIAL MODEL: "INDUSTRIAL BUILDING BOARD"- REACTION TO FIRE: A1 – THERMAL CONDUCTIVITY (λ): 0.037 W/mK - THICKNESS LEVEL: T3 - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD - FACING: UNFACED. - WATER ABSORPTION CLASS: WS THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 24.10.2018)
10. COMMERCIAL MODEL: "INDUSTRIAL BUILDING BOARD R+"- REACTION TO FIRE: A1, - THERMAL CONDUCTIVITY (λ): 0.035 W/mK - THICKNESS LEVEL: T3- DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD - FACING: UNFACED. - WATER ABSORPTION CLASS: WS. THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 24.10.2018)
11. COMMERCIAL MODEL: "FACADE BOARD" - REACTION TO FIRE: A1 - THERMAL CONDUCTIVITY (λ): 0.035 W/mK - THICKNESS LEVEL: T3 - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD - FACING: GLASSTISSUE FACED - WATER ABSORPTION CLASS: WS. THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 24.10.2018)
12. COMMERCIAL MODEL: "ROOF BLANKET" (TYPE 300+) - REACTION TO FIRE: A1, - THERMAL CONDUCTIVITY (λ) :0.035 W/mK - THICKNESS LEVEL: T1 - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD - FACING: UNFACED. THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 26.05.2022)
13) COMMERCIAL MODEL: "PREFABRICATED BUILDING BLANKET", -REACTION TO FIRE: A1, -THERMAL CONDUCTIVITY (λ) :0.045 W/mK, -THICKNESS LEVEL: T1, - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD, - FACING: UNFACED. THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 26.12.2023)
14) COMMERCIAL MODEL: OPTIMA SMART, -REACTION TO FIRE: A1, -THERMAL CONDUCTIVITY (λ) :0.037

e-imzalı/e-signed

11.05.2026

On Behalf Of The Head Of Certification Center
FATİH KURT

TSE ADANA CERTIFICATION DIRECTOR

*This certificate also shows that the production place of the certified product meets the requirements of Institute.
*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.
*TSE * Address: Yakapınar Mah. D-400 Bulvarı No:174 Yüreğir * Telephone: 03224581940-41* Fax: 03224588243
*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail :bmb@tse.org.tr , web : www.tse.org.tr

TÜRK STANDARDLARI ENSTİTÜSÜ

TÜRK STANDARDLARINA UYGUNLUK BELGESİ

TURKISH STANDARDS INSTITUTION

CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS

Markanın Tanımı Description of the Mark

TSE veya/or  veya/or TSE

(000134-TSE-06/09nolu belge devamı) : İZOCAM TİCARET VE SANAYİ ANONİM ŞİRKETİ

İLGİLİ TÜRK STANDARDI(*RELATED TURKISH STANDARD*) TS EN 13162+A1 / 02.04.2015

W/mK, -THICKNESS LEVEL: T1, - DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD, - FACING: UNFACED. THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 26.12.2023)

15- COMMERCIAL MODEL: OPTIMA SMART S, -REACTION TO FIRE: A1, THERMAL CONDUCTIVITY (λ): 0,039 W/mK, -THICKNESS LEVEL: T1, DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE: NPD, - FACING: UNFACED, THESE PRODUCTS CANNOT BE USED FOR SPECIAL APPLICATIONS THAT REQUIRE COMPRESSIVE CREEP. (Scope Change: 30.12.2025)

e-imzalı/e-signed

11.05.2026

On Behalf Of The Head Of Certification Center
FATİH KURT

TSE ADANA CERTIFICATION DIRECTOR

*This certificate also shows that the production place of the certified product meets the requirements of Institute.
*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.
*TSE * Address: Yakapınar Mah. D-400 Bulvarı No:174 Yüreğir * Telephone: 03224581940-41* Fax: 03224588243
*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail :bmb@tse.org.tr , web : www.tse.org.tr